


Certified Product, No Modifications
 Permitted Without Review Drawing
 Numbers
 12310GEX Rev 16 (IECEX Drawing),
 1000061 CSA Rev 5

CSA INFORMATION

ASSEMBLIES WILL CARRY THE FOLLOWING INFORMATION




To Be Connected To A Class 2 Circuit Only
 "Raccorder Uniquement A Un Circuit De Classe 2"

INSTALLATION INSTRUCTIONS

1. FASTEN SOLENOID TO HYDRAULIC SUB-ASSEMBLY
2. TIGHTEN NUT WITH AID OF A TOOL TO 8 Nm (6.5 FT.LBS)
3. CONNECT WIRES TO APPROPRIATE CONNECTIONS AS SHOWN ON THE MACHINE WIRING DIAGRAM

INCLUDES WEEK AND YEAR

Excell Manufacturing Solutions, Ohio-USA
 Type No. 12310GEX-1-22W-YC
 Serial # XXXXXX
 Ambient Range -50°C to +40°C
 24 VDC, 0.93 AMPS



**Class I, Divison 1, Groups A, B, C and D
 Ex mb IIC, T3; Enclosure Rating IP67
 Class I, Zone 1, AEx mb IIC
 Class II, Division 1, Groups E, F and G; Class III Division 1
 Conformity Against NEC 500/505 As Applicable**

MAINTENANCE INSTRUCTIONS

1. INSPECT SOLENOID ASSEMBLY FOR FRACTURES OR CRACKS
2. INSPECT CABLE ENTRY AREA FOR DAMAGED OR EXPOSED WIRES
3. ENSURE THE SOLENOID CARRIES A CERTIFICATION LABEL THAT IDENTIFIES IT SUITABLE FOR USE IN HAZARDOUS LOCATIONS

SPECIAL CONDITIONS FOR SAFE USE

THE PERMANENTLY CONNECTED POWER CABLE SHALL BE TERMINATED IN A MANNER THAT IS SUITABLE FOR THE ENVIRONMENT WHERE IT IS BEING USED.

IF IT IS TERMINATED IN A HAZARDOUS AREA APPROPRIATE EXPLOSION PROTECTION SHALL BE PROVIDED.

1000053

REVISION HISTORY			
REV	DESCRIPTION	DATE	APPROVED
1	RELEASED INSTRUCTION SHEET	5/20/2013	MSB
2	Updated Cert Numbers, Address	10/22/2014	MSB
3	Updated Cert Revisions	11/24/2014	MSB
4	Cert #, Changed Label	12/8/2014	MSB
5	Updated Cert Revision, Temp. Rate	3/11/2015	MSB

DRAWN Paquin	2/12/2013	Excell Manufacturing Solutions, LLC 9286 Mercantile Dr. Mentor, Ohio 44060 (216) 261-5700		
CHECKED		TITLE INSTRUCTION SHEET (22 Watts) With Yellow Chromate Plating		
QA		SIZE C	DWG NO 1000061 CSA i Rev 5	REV 5
MFG		SCALE	SHEET 1 OF 1	
APPROVED				